



Digital Panel Meters

truly world class

Features:

- Flicker-free LED
- Pre-calibrated meters
- Latest LSI IC technology
- Auto Polarity and Auto Zero
- Compact Design
- Robust Terminals
- Solid-state circuitry
- Prompt service support
- International Styling

Parameters:

- AC Volt
- DC Volt
- AC Current
- DC Current
- Frequency
- Temperature
- RPM
- Percentage
- Weight
- Length
- etc.

Specification:

Aux Supply	: a) Nominal 240 V AC (170-270 V AC) b) Universal Input (85-265 V AC/DC)
Accuracy	: Class 1 [+/- (1% of full scale + 1 count)] For Hz. meter: 0.1/0.01 Hz.
Resolution	: 1 count in 100 counts or better
Display	: 3 ½ / 3 digits
Burden	: 0.2 VA max. 3 VA max. on Auxiliary supply
Ambient	: 0-50 ° C humidity < 95%
Weight	: 320-700gms depending on model
Dimension	: 48X96, 96X96, 72X72



15.02.2004

 **BAID POWER SERVICES P. LTD.**

152, Block- B, Ground floor, Lake Town, Kolkata - 700089 Tel:+91(033)25212503, Fax:+91(033)25343662
Email: info@indiapowerhouse.net, Web: www.indiapowerhouse.com